


Dual INT-A-PAK Low Profile “Half Bridge” (Standard Speed IGBT), 400 A



Dual INT-A-PAK Low Profile

PRODUCT SUMMARY	
V_{CES}	600 V
I_C DC at $T_C = 25\text{ }^\circ\text{C}$	750 A
$V_{CE(on)}$ (typical) at 400 A, $25\text{ }^\circ\text{C}$	1.24 V
Speed	DC to 1 kHz
Package	DIAP low profile
Circuit	Half bridge

FEATURES

- Gen 4 IGBT technology
- Standard: optimized for hard switching speed
- Low $V_{CE(on)}$
- Square RBSOA
- HEXFRED® antiparallel diode with ultrasoft reverse recovery characteristics
- Industry standard package
- Al_2O_3 DBC
- UL approved file E78996 
- Designed for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

BENEFITS

- Increased operating efficiency
- Performance optimized as output inverter stage for TIG welding machines
- Direct mounting on heatsink
- Very low junction to case thermal resistance

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	V_{CES}		600	V
Continuous collector current	$I_C^{(1)}$	$T_C = 25\text{ }^\circ\text{C}$	750	A
		$T_C = 80\text{ }^\circ\text{C}$	525	
Pulsed collector current	I_{CM}		1000	
Clamped inductive load current	I_{LM}		1000	
Diode continuous forward current	I_F	$T_C = 25\text{ }^\circ\text{C}$	219	
		$T_C = 80\text{ }^\circ\text{C}$	145	
Gate to emitter voltage	V_{GE}		± 20	V
Maximum power dissipation (IGBT)	P_D	$T_C = 25\text{ }^\circ\text{C}$	1563	W
		$T_C = 80\text{ }^\circ\text{C}$	875	
RMS isolation voltage	V_{ISOL}	Any terminal to case (V_{RMS} $t = 1$ s, $T_J = 25\text{ }^\circ\text{C}$)	3500	V

Note

⁽¹⁾ Maximum continuous collector current must be limited to 500 A to do not exceed the maximum temperature of terminals



ELECTRICAL SPECIFICATIONS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{BR(CES)}$	$V_{GE} = 0\text{ V}, I_C = 500\text{ }\mu\text{A}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}, I_C = 300\text{ A}$	-	1.14	1.35	
		$V_{GE} = 15\text{ V}, I_C = 400\text{ A}$	-	1.24	1.52	
		$V_{GE} = 15\text{ V}, I_C = 300\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.08	1.29	
		$V_{GE} = 15\text{ V}, I_C = 400\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.21	1.5	
Gate threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}, I_C = 250\text{ }\mu\text{A}$	3.0	4.6	6.3	
Collector to emitter leakage current	I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}$	-	0.075	1	mA
		$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 125\text{ }^\circ\text{C}$	-	1.8	10	
Diode forward voltage drop	V_{FM}	$I_{FM} = 300\text{ A}$	-	1.48	1.75	V
		$I_{FM} = 400\text{ A}$	-	1.63	1.98	
		$I_{FM} = 300\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.50	1.77	
		$I_{FM} = 400\text{ A}, T_J = 125\text{ }^\circ\text{C}$	-	1.70	2.04	
Gate to emitter leakage current	I_{GES}	$V_{GE} = \pm 20\text{ V}$	-	-	± 200	nA

SWITCHING CHARACTERISTICS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Turn-on switching loss	E_{on}	$I_C = 400\text{ A}, V_{CC} = 360\text{ V}, V_{GE} = 15\text{ V}, R_g = 1.5\text{ }\Omega, L = 500\text{ }\mu\text{H}, T_J = 25\text{ }^\circ\text{C}$	-	8.5	-	mJ
Turn-off switching loss	E_{off}		-	113	-	
Total switching loss	E_{tot}		-	121.5	-	
Turn-on switching loss	E_{on}	$I_C = 400\text{ A}, V_{CC} = 360\text{ V}, V_{GE} = 15\text{ V}, R_g = 1.5\text{ }\Omega, L = 500\text{ }\mu\text{H}, T_J = 125\text{ }^\circ\text{C}$	-	21	-	ns
Turn-off switching loss	E_{off}		-	163	-	
Total switching loss	E_{tot}		-	184	-	
Turn-on delay time	$t_{d(on)}$		-	532	-	
Rise time	t_r		-	377	-	
Turn-off delay time	$t_{d(off)}$		-	496	-	
Fall time	t_f	-	1303	-		
Reverse bias safe operating area	RBSOA	$T_J = 150\text{ }^\circ\text{C}, I_C = 1000\text{ A}, V_{CC} = 400\text{ V}, V_P = 600\text{ V}, R_g = 22\text{ }\Omega, V_{GE} = 15\text{ V to }0\text{ V}, L = 500\text{ }\mu\text{H}$	Fullsquare			
Diode reverse recovery time	t_{rr}	$I_F = 300\text{ A}, di_F/dt = 500\text{ A}/\mu\text{s}, V_{CC} = 400\text{ V}, T_J = 25\text{ }^\circ\text{C}$	-	150	179	ns
Diode peak reverse current	I_{rr}		-	43	59	A
Diode recovery charge	Q_{rr}		-	3.9	6.3	μC
Diode reverse recovery time	t_{rr}	$I_F = 300\text{ A}, di_F/dt = 500\text{ A}/\mu\text{s}, V_{CC} = 400\text{ V}, T_J = 125\text{ }^\circ\text{C}$	-	236	265	ns
Diode peak reverse current	I_{rr}		-	64	80	A
Diode recovery charge	Q_{rr}		-	8.6	11.1	μC



THERMAL AND MECHANICAL SPECIFICATIONS					
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS
Operating junction and storage temperature range	T_J, T_{Stg}	-40	-	150	$^{\circ}\text{C}$
Junction to case per leg	IGBT	-	-	0.08	$^{\circ}\text{C}/\text{W}$
	Diode	-	-	0.4	
Case to sink per module	R_{thCS}	-	0.05	-	
Mounting torque	case to heatsink: M6 screw	4	-	6	Nm
	case to terminal 1, 2, 3: M5 screw	2	-	4	
Weight		-	270	-	g




Fig. 1 - Typical Output Characteristics, $T_J = 25^{\circ}\text{C}$, $V_{GE} = 15\text{ V}$




Fig. 3 - Maximum DC IGBT Collector Current vs. Case Temperature




Fig. 2 - Typical Output Characteristics, $T_J = 125^{\circ}\text{C}$






Fig. 4 - Typical IGBT Collector to Emitter Voltage vs. Junction Temperature, $V_{GE} = 15\text{ V}$




93363_05

Fig. 5 - Typical IGBT Transfer Characteristics




93363_08

Fig. 8 - Typical IGBT Zero Gate Voltage Collector Current




93363_06

Fig. 6 - Typical IGBT Gate Threshold Voltage




93363_09

Fig. 9 - Typical Diode Forward Characteristics




93363_07

Fig. 7 - IGBT Reverse Bias SOA,
 $T_J = 150\text{ °C}$, $V_{GE} = 15\text{ V}$, $R_g = 22\ \Omega$




93363_10

Fig. 10 - Maximum DC Forward Current vs. Case Temperature




93363_11

Fig. 11 - Typical IGBT Energy Loss vs. I_C ,
 $T_J = 125\text{ }^\circ\text{C}$, $V_{CC} = 360\text{ V}$, $R_g = 1.5\ \Omega$,
 $V_{GE} = 15\text{ V}$, $L = 500\ \mu\text{H}$




93363_14

Fig. 14 - Typical IGBT Switching Time vs. R_g ,
 $T_J = 125\text{ }^\circ\text{C}$, $I_C = 400\text{ A}$, $V_{CC} = 360\text{ V}$,
 $V_{GE} = 15\text{ V}$, $L = 500\ \mu\text{H}$




93363_12

Fig. 12 - Typical IGBT Switching Time vs. I_C ,
 $T_J = 125\text{ }^\circ\text{C}$, $V_{CC} = 360\text{ V}$, $R_g = 1.5\ \Omega$,
 $V_{GE} = 15\text{ V}$, $L = 500\ \mu\text{H}$




93363_15

Fig. 15 - Typical Reverse Recovery Time vs. di_F/dt ,
 $V_{CC} = 400\text{ V}$, $I_F = 300\text{ A}$




93363_13

Fig. 13 - Typical IGBT Energy Loss vs. R_g ,
 $T_J = 125\text{ }^\circ\text{C}$, $I_C = 400\text{ A}$, $V_{CC} = 360\text{ V}$,
 $V_{GE} = 15\text{ V}$, $L = 500\ \mu\text{H}$




93363_16

Fig. 16 - Typical Reverse Recovery Current vs. di_F/dt ,
 $V_{CC} = 400\text{ V}$, $I_F = 300\text{ A}$




93363_17

Fig. 17 - Typical Reverse Recovery Charge vs. di_F/dt ,
 $V_{CC} = 400\text{ V}$, $I_F = 300\text{ A}$



93363_18

Fig. 18 - Maximum Thermal Impedance Z_{thJC} Characteristics (IGBT)




93363_19

Fig. 19 - Maximum Thermal Impedance Z_{thJC} Characteristics (Diode)

ORDERING INFORMATION TABLE

Device code	G	A	400	T	D	60	S		
	①	②	③	④	⑤	⑥	⑦		
	1	-	Insulated Gate Bipolar Transistor (IGBT)	2	-	A = Generation 4 IGBT	3	-	Current rating (400 = 400 A)
	4	-	Circuit configuration (T = Half-bridge)	5	-	Package indicator (D = Dual INT-A-PAK Low Profile)	6	-	Voltage rating (60 = 600 V)
	7	-	Speed/type (S = Standard Speed IGBT)						

CIRCUIT CONFIGURATION

LINKS TO RELATED DOCUMENTS

Dimensions	www.vishay.com/doc?95435
------------	--



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.