
KEMET Part Number: CK06BX104K

(C062K104K1X5CA)



Ceramic, Military/High Reliability, MIL-11015, 0.1 uF, 10%, 100 V, BX, N/A, Lead Spacing = 5.08mm



| Dimensions | | |
|------------|--------------------|--|
| L | 7.37mm +/-0.25mm | |
| Н | 7.37mm +/-0.25mm | |
| Т | 2.29mm +/-0.25mm | |
| S | 5.08mm +/-0.38mm | |
| LL | 31.75mm MIN | |
| F | 0.635mm +/-0.051mm | |

| Packaging Specifications | | |
|--------------------------|-----------|--|
| Packaging: | Bulk, Bag | |
| Packaging Quantity: | 100 | |

| General Information | |
|--------------------------|---|
| Style: | Radial |
| Series: | MIL-11015 |
| RoHS: | No |
| Termination: | Lead (SnPb) |
| Failure Rate: | N/A |
| Testing and Reliability: | MIL-PRF-11015 |
| Approvals: | MIL-PRF-11015 |
| Notes: | Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk |

| Specifications | | |
|--------------------------|-----------|--|
| Capacitance: | 0.1 uF | |
| Capacitance Tolerance: | 10% | |
| Voltage DC: | 100 VDC | |
| Temperature Range: | -55/+125C | |
| Temperature Coefficient: | BX | |
| Dissipation Factor: | 2.5% | |
| Insulation Resistance: | 10 GOhms | |
| Dielectric Strength: | 250 V | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

